

Fast assembly concealed hinge

- ▶ Sensys thick door hinge, door thickness up to 32 mm
- ▶ Opening angle 95°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 2
- ▶ For door thickness 15 - 32 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel in obsidian black

Drilling pattern	full overlay (Base B 12.5 mm)	half overlay (Base B 3 mm)	inset (Base B -4 mm)

With integrated Silent System, with self closing feature (Sensys 8631i)

Cup assembly	Mounting hole ø x T mm	full overlay		half overlay	inset
		50 ea.	200 ea.	50 ea.	50 ea.
For screwing on	-	9 091 753	9 090 967	9 091 755	9 091 756
with expanding sockets	ø 10 x 11	9 091 754		9 091 785	9 091 757

Without Silent System, without self closing feature, for handleless applications (Sensys 8661)

Cup assembly	Mounting hole ø x T mm	full overlay	half overlay	inset
		50 ea.	50 ea.	50 ea.
For screwing on	-	9 091 758	9 091 759	9 091 760
with expanding sockets	ø 10 x 11	9 091 786	9 091 787	9 091 788