


Fast assembly concealed hinge

- ▶ Sensys angle hinge W90
- ▶ Opening angle 95°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 28 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated adjustment of door offset +1 mm / -2 mm
- ▶ Integrated reveal adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel, nickel plated

Drilling pattern



inset
(Base B 4 mm)



With integrated Silent System, with self closing feature (Sensys 8639i W90)

Mounting option	Mounting hole ø x T mm	inset 50 ea.
for screwing on	-	9 088 021
for pressing in	ø 10 x 11	9 088 039
Fix fast assembly	ø 10 x 6	9 088 075

Without Silent System, with self closing feature (Sensys 8639 W90)

Mounting option	Mounting hole ø x T mm	inset 50 ea.
for screwing on	-	9 088 105
for pressing in	ø 10 x 11	9 088 123
Fix fast assembly	ø 10 x 6	9 088 141

Without Silent System, without self closing feature, for handleless applications (Sensys 8669 W90)

Mounting option	Mounting hole ø x T mm	inset 50 ea.
for screwing on	-	9 088 181
for pressing in	ø 10 x 11	9 088 199
Fix fast assembly	ø 10 x 6	9 088 217



hettich.com/short/260da9