


Fast assembly concealed hinge

- ▶ Sensys wide angle hinge, with zero protrusion
- ▶ Opening angle 165°, drilling pattern TH 52 x 5.5 mm



- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 24 mm
- ▶ Cup depth 11.6 mm
- ▶ Integrated overlay adjustment +2 mm / -2 mm
- ▶ Integrated depth adjustment +3 mm / -2 mm
- ▶ Height adjustment at mounting plate
- ▶ Steel / nickel plated die-cast zinc

Drilling pattern



full overlay (Base B 12.5 mm)



half overlay (Base B 3 mm)



With self closing feature (Sensys 8657)

Cup assembly	Mounting hole $\varnothing \times T$ mm	full overlay	half overlay
		50 ea.	50 ea.
For screwing on	-	9 099 750	9 099 760
For pressing in	$\varnothing 10 \times 11$	9 099 751	9 099 761
with expanding sockets	$\varnothing 10 \times 11$	9 099 756	9 099 766

Without Silent System, for handleless applications (Sensys 8687)

Cup assembly	Mounting hole $\varnothing \times T$ mm	full overlay	half overlay
		50 ea.	50 ea.
For screwing on	-	9 099 810	9 099 820
For pressing in	$\varnothing 10 \times 11$	9 099 811	9 099 821
with expanding sockets	$\varnothing 10 \times 11$	9 099 816	9 099 826